

Reliable sterile filtration. Consistent cultures.



The Life Science business
of Merck operates as
MilliporeSigma in the
U.S. and Canada.

Millipore®

Preparation, Separation,
Filtration & Monitoring Products

Millipore® – the name you trust for sterile filtration

Millipore® is the brand of choice for sterile filters—for everything from media preparation for your cell culture, to sterilization of critical drug compounds:

Selection

From 1 mL to 20 L, we offer an array of both vacuum- and pressure-driven devices that incorporate our long-trusted membrane technology.

Expertise

With over 50 years of expertise in the sterile filtration business, we set the industry standard for high performance membrane technology and application in sterile filtration.

Innovation

As protocols requiring sterile filtration evolve, we continually qualify our filter systems to provide application-specific data.

Improving on Sustainability

We offer Stericup® E and Steritop® E sterile filtration devices, designed to ensure trouble-free cell culture, while diminishing environmental impact. Groundbreaking device design maintains exceptional Stericup® filtration while dramatically reducing the use of disposable plastic and packaging materials. (see p. 8)

Membrane Technology

Sterile filtration performance depends on the quality of the membranes used. Our Millipore Express® PLUS, Durapore®, MF-Millipore™ and Fluoropore™ brand membranes set the industry standard for their application-specific properties (see below).

To learn more, please visit:


SigmaAldrich.com/membrane-center

Fit-for-Application Membrane Chemistries


- Fastest flow, low protein-binding of aqueous solutions with Millipore Express® and Express® PLUS polyethersulfone (PES) membrane devices
- Fast flow and low protein-binding Mixed Cellulose Esters (MCE)
- Broad chemical compatibility and very low protein-binding polyvinylidene fluoride (PVDF)

To learn more, visit:


SigmaAldrich.com/SterileFiltration



A. Amount of ¹²⁵I-goat IgG bound per square area of PES filters from different sterile vacuum filtration devices. The amount of bound IgG protein ranged from ~24 µg/cm² to 170 µg/cm². The PES filter from the Stericup® sterile vacuum filtration device exhibited the lowest binding of all devices tested. More information at: SigmaAldrich.com/Protein-Binding



B. Calculated flux for 0.1 and 0.22 µm PES and PVDF membrane filters. VP = 0.1 µm PES membrane. GP = 0.22 µm PES membrane. GV = 0.22 µm PVDF membrane. VV = 0.1 µm PVDF membrane. More information at: SigmaAldrich.com/Mycoplasma-Clearance



C. Flow rate comparison for the sterile filtration of FBS. Brand CS had the lowest flow rate at 4.49mL/sec, followed by Brand NS (6.72mL/sec), Stericup® Quick Release (7.80mL/sec), and Brand PF with the highest flow rate at 8.44mL/sec. More information at: SigmaAldrich.com/FBS-Filtration

Table of Contents

Summary of Sterile Filtration Products	4
Bench-scale Filters	6
Stericup® and Steritop® Quick Release Filter Units	7
Stericup® E and Steritop® E Eco-Friendly Filter Units	8
Steriflip® Filter Units	10
Millex® Syringe Filters	11
Large-scale Sterile Filtration Devices	13
Sterivex® Filters	13
Stericap™ PLUS Filters	13
Steripak™ Filters	14
Accessories for Stericup® and Steritop® Systems	14
Related Products: Multiwell Plates	15
MultiScreen® _{HTS} Filter Plates	15
Millicell® Microporous Membrane-Based Cell Culture	15



Click on
 Learn more

What people are saying...

"For over 40 years we've trusted MilliporeSigma to provide the quality filtration tools we need."

James T. Voss, NRRPT, CHP Fellow, Health Physics Society, President of Voss Associates.

"Trusted partners like MilliporeSigma are rare but central to our success."

Dr. Michael West, CEO, BioTime, Inc., Renowned thought leader in stem cell therapeutics

"I found that both the Stericup® E and Steritop® E were incredibly easy to use. I really appreciate that both the Stericup® E and Steritop® E are designed to reduce plastic use in the lab without compromising performance. The Stericup® E and Steritop® E are an ideal way for our lab to address some of the criteria outlined by LEAF (Laboratory Efficiency Assessment Framework) which helps us progress toward more sustainable practices in the lab."

Bianca Briscas, University of NSW

Summary of Sterile Filtration Products

Vacuum filtration devices for cell culture media preparation

Description	Pore Size (µm)	Membrane	Maximum Process Volume	
Stericup® Quick Release Filtration	0.1	Millipore Express® PLUS (PES), Durapore® (PVDF)	150 mL	
	0.22		250 mL	
	0.45		500 mL	
			1000 mL	
Steritop® Quick Release Bottle-Top Filtration Units	0.1	Millipore Express® PLUS (PES), Durapore (PVDF)	150 mL	
	0.22		250 mL	
			500 mL	
			1000 mL	
 Stericup® E Eco-Friendly Filtration Units	0.22	Millipore Express® PLUS (PES)	500 mL 1000 mL	
 Steritop® E Eco-Friendly Bottle-Top Filtration Units	0.22	Millipore Express® PLUS (PES)	All Volumes	
Steriflip® Filtration Units	0.22 0.45	Millipore Express® PLUS (PES), Durapore® (PVDF), Nylon Net	50 mL	
Click Seal Receiver Bottles and Caps			100 mL 250 mL 500 mL	

Sterile syringe filters for cell culture media preparation and small volume filtration

Description	Pore Size (µm)	Membrane	Maximum Process Volume	
Millex® Syringe Filters (4, 13, 25 mm)	0.2	Millipore Express® PLUS (PES), Durapore® (PVDF), MCE, hydrophilic PTFE	1 – 100 mL	
	0.22			
	0.45			
	0.8			
	5.0			
Millex® Syringe Filters (33 mm)	0.1	Millipore Express® PLUS (PES), Durapore® (PVDF), MCE	10 – 200 mL	
	0.22			
	0.45			

Large-scale sterile filtration devices

Description	Pore Size (µm)	Membrane	Maximum Process Volume	
Stericap™ PLUS Vacuum-driven Filters	0.22	Millipore Express® PLUS (PES)	2 – 10 L	
Sterivex® Pressure-driven Filters	0.22 0.45	Millipore Express® PLUS (PES), Durapore® (PVDF)	Up to 2 L	
Millex®-GP 50 mm Pressure-driven Filters	0.22	Millipore Express® PLUS (PES)	Up to 4 L	
Steripak™ Pressure-driven Filters	0.22	Millipore Express® PLUS (PES)	10 L 20 L	

Hydrophobic filters for gas filtration

Description	Pore Size (µm)	Inlet-Outlet Fittings	Membrane	
Dualex™ and Millex®-FG 25 mm Syringe Filters	0.2 0.22	FLL-MLS, FLL-MLL, FLS-MLS, FLL-Spike	Hydrophobic PTFE, Hydrophobic PVDF	
Millex® 50 mm for gas filtration and protection of vacuum pumps	0.2 0.45 1.0	Stepped hose barb and/or 1/8 in. NPTM	Hydrophobic PTFE	

FLL = Female Luer-Lok®

FLS = Female Luer slip

MLL = Male Luer-Lok®

MLS = Male Luer slip



Bench-scale Filters

Stericup® & Steritop® Filter Units

Stericup® and Steritop® sterile filtration devices combine superior flow rates and throughput with low non-specific binding and a stable, no-tip design.

Fast flow, low-binding membranes

Membranes with low protein binding ensure that key growth factors and proteins won't be absorbed onto the filter. Millipore Express® PLUS membranes feature low protein binding and faster flow than other membranes. For applications that require ultra-low protein binding, use a device with a Durapore® PVDF membrane.

Stericup® Quick Release Filtration Systems

Work With Ease. Filter With Confidence.


Stericup® Quick Release Filtration Systems streamline your workflow with ergonomic design updates and safeguard your results with the proven performance of Millipore membranes.

- 1 Quarter-Turn Quick Release Funnel Removal
- 2 Frosted Writing Surface
- 3 Lighter Color for Legibility
- 4 Click-Seal Confidence Cap

Additional Features:

- Cap Rests on the Side to Avoid Risk of Contamination
- Stackable Bottles to Save Space

Learn more about Stericup® Quick Release Filtration Systems at:
SigmaAldrich.com/StericupQuickRelease



Stericup® Filter Units

Stericup® Filtration Systems combine a filter unit with a receiver flask and cap for processing and storage.

Description	Membrane/Application	Pore Size (µm)	Funnel Capacity (mL)	Receiver Bottle (mL)	Qty/Pk	Cat No.
Stericup®-GP Quick Release Filter Units†	Millipore Express® PLUS (PES)/fast filtration of tissue culture media and buffers	0.22	150	150	12	S2GPU01RE
			250	250	12	S2GPU02RE
			500	500	12	S2GPU05RE
			500	1000	12	S2GPU10RE
			1000	1000	12	S2GPU11RE
Stericup®-HV Quick Release Filter Units	Durapore®(PVDF)/filtration of high value biomolecules, lowest protein binding	0.45	150	150	12	S2HVVU01RE
			250	250	12	S2HVVU02RE
			500	500	12	S2HVVU05RE
			1000	1000	12	S2HVVU11RE
Stericup®-VP Quick Release Filter Units	Millipore Express® (PES) / removal of mycoplasma*	0.1	250	250	12	S2VPU02RE
			1000	1000	12	S2VPU11RE
Stericup®-GV Quick Release Filter Units	Durapore® (PVDF) / filtration of high value biomolecules, lowest protein binding	0.22	150	150	12	S2GVU01RE
			250	250	12	S2GVU02RE
			500	500	12	S2GVU05RE
			500	1000	12	S2GVU10RE
			1000	1000	12	S2GVU11RE

Steritop® Filter Units

Steritop® bottle-top filter units can be used on bottles with 33 mm or 45 mm thread.

Description	Membrane/Application	Pore Size (µm)	Funnel Capacity (mL)	Thread Size (mm)	Qty/Pk	Cat No.
Steritop® QR Filter Units†	Millipore Express® PLUS (PES)/fast filtration of tissue culture media and buffers	0.22	150	45	12	S2GPT01RE
			250	45	12	S2GPT02RE
			500	45	12	S2GPT05RE
			1000	45	12	S2GPT10RE
Steritop®-GP Filter Units	Millipore Express® PLUS (PES) / filtration of high value biomolecules, lowest protein binding	0.22	150	33	12	SCGPS01RE
			250	33	12	SCGPS02RE
			500	33	12	SCGPS05RE
Steritop®-GV Filter Units	Durapore® (PVDF) / filtration of high value biomolecules, lowest protein binding	0.22	500	45	12	S2GVT05RE
Steritop®-VP Filter Units	Millipore Express® (PES)/ removal or mycoplasma*	0.1	1000	45	12	S2VPT10RE
Click Seal Receiver Bottles and Caps			250	45	12	S200B02RE
			500	45	12	S200B05RE
			1000	45	12	S200B10RE

* 0.10 µm pore size is designed to enhance maximum filtration of tissue culture media but it is not a guarantee of complete mycoplasma removal.

† Selected stem cell research publications citing Stericup® or Steritop® device for sterile filtration of medium:

1. Feeder independent culture of human embryonic stem cells. Teneille E. Ludwig et al. Nature Methods Vol. 3 No. 8 August 2006 637-646.
2. Roelandt P et al. Differentiation of rat multipotent adult progenitor cells to functional hepatocyte-like cells by mimicking embryonic liver development. Nat Protoc. 2010 Jul;5(7):1324-36.
3. Hu BY et al. Differentiation of human oligodendrocytes from pluripotent stem cells. Nat Protoc. 2009;4(11):1614-22. Epub 2009 Oct 15.
4. Hu BY, Zhang SC. Differentiation of spinal motor neurons from pluripotent human stem cells. Nat Protoc. 2009;4(9):1295-304.
5. Bigdeli N et al. Adaptation of human embryonic stem cells to feeder-free and matrix-free culture conditions directly on plastic surfaces. J Biotechnol. 2008 Jan 1;133(1):146-53.
6. Dravid G et al. Culture of human embryonic stem cells on human and mouse feeder cells. Methods Mol Biol. 2006;331:91-104.

Stericup® E and Steritop® E Eco-Friendly Filter Units

Description	Membrane/Application	Pore Size (µm)	Receiver Bottle (mL)	Thread Size (mm)	Qty/Pk	Cat No.
 Stericup® E-GP Sterile Vacuum Filtration System	Millipore Express® PLUS (PES)/fast filtration of tissue culture media and buffers	0.22	500	38	12	SEGPU0538
			500	45	12	SEGPU0545
			1000	38	12	SEGPU1138
			1000	45	12	SEGPU1145
 Steritop® E-GP Sterile Vacuum Filtration System	Millipore Express® PLUS (PES)/fast filtration of tissue culture media and buffers	0.22		38	12	SEGPT0038
				45	12	SEGPT0045



Stericup® E & Steritop® E Filter Systems

The new 'E' (eco-friendly) additions to the Stericup® family eliminate the plastic filter funnel entirely by threading directly onto the media bottle. Stericup® E and Steritop® E filter devices reduce environmental impact by cutting down on:

- Disposable plastic
- Hazardous waste
- Lab storage space requirements



Usage Guidelines

- Choose a collar thread (38 mm or 45 mm) that is compatible with your glass or plastic media/ buffer bottle.
- The 38 mm thread is recommended for our media bottles and majority of other standard commercial media bottles.
- The 45 mm thread is recommended for wider neck media bottles (such as Gibco®) or 45mm thread glass bottles.
- Use only glass or plastic bottles designed for vacuum applications. For the Steritop® E filter, use a 45 mm threaded glass or plastic receiver bottle no larger than 2 liters.

Your eco-impact, by the numbers:

	Plastics*	Packaging*
Stericup® E Sterile filter Eliminates disposable filler funnel	 Up to 26%	 Up to 20%
Steritop® E Sterile filter Eliminates disposable filler funnel & receiver bottle	 Up to 48%	 Up to 69%



Both Stericup® E and Steritop® E sterile filters thread directly onto virtually any commercial media bottle or glass bottle



Stericup® E products use significantly less packaging made from materials that reduce environmental impact



Learn more about the Stericup® E and the Steritop® E at: SigmaAldrich.com/Stericup-E

Learn more about our commitment to responsible life science tools at SigmaAldrich.com/green

Stericup® E and Steritop® E Filter Units Sustainability Checklist



Stericup® E and Steritop® E filters thread directly onto any commercial media bottle or glass bottle:

- Reduces plastic and hazardous waste.
- Frees-up storage in smaller tissue culture rooms, where space is at a premium.
- Enhances laboratory compliance with institutional sustainability requirements—or a means for achieving individual environmental responsibility goals.

Stericup® E and Steritop® E filters have the Accountability, Consistency, and Transparency (ACT) Environmental Impact Factor Label, published by My Green Lab®, providing a score based around manufacturing, energy and water use, packaging and end-of-life. The ACT labelled products help labs choose greener life science products. The ACT labels can be viewed on the product pages of each Stericup® E and Steritop® E filter catalogue number; please visit [SigmaAldrich.com](https://www.sigmaaldrich.com).

Stericup® E and Steritop® E filters are packaged in individual, recyclable pouches for sterility.

Stericup® E and Steritop® E user guides are accessible via [SigmaAldrich.com](https://www.sigmaaldrich.com) or by scanning the QR code on the product label or box, to reduce paper waste.

The Stericup® E and Steritop® E corrugated boxes and dividers have sustainable forestry certification.

Difference between Stericup® Quick Release and Stericup® E Filter Units

Product	Funnel	Filter Collar	Receiver Bottle
 <p>Stericup® Quick Release Filtration</p>			
 <p>Steritop® Quick Release Bottle-Top Filtration Units</p>			
 <p>Stericup® E Eco-Friendly Filtration and Storage Units</p> <p>Greener Solution</p>			
 <p>Steritop® E Eco-Friendly Bottle-Top Filtration Units</p> <p>Greener Solution</p>			

Steriflip® Filter Units

For filtering 10 mL to 50 mL volumes without sample transfer steps.

Filter up to 50 mL directly into a centrifuge tube

- Attach the device to a standard 50 mL centrifuge tube containing your sample, flip it over and apply vacuum
- Filtrate collects in the attached 50 mL tube
- Available with optional funnel accessory



Description	Membrane	Pore Size (µm)	Qty/Pk	Cat No.
Steriflip®-GP Filter Unit	Millipore Express® PLUS (PES)	0.22	25	SCGP00525
Steriflip®-GV Filter Unit	Durapore® (PVDF)	0.22	25	SE1M179M6
Steriflip®-HV Filter Unit	Durapore® (PVDF)	0.45	25	SE1M003M00
Steriflip® Steri-Strainer	Nylon Net	100	25	SCNY00100
		60	25	SCNY00060
		40	25	SCNY00040
		20	25	SCNY00020
Accessory				
Steriflip® Funnel Attachment			25	SC50FL025



Sterile Millex® Syringe Filters

Millex® syringe filters provide convenient sterilization of small volumes and are ideal for solutions such as antibiotics and tissue culture additives. Their unsurpassed quality and consistency of results has led to the development of many sample preparation methods that specify Millex® filters.

Manufactured for reliable performance

Manufacturing occurs in a controlled environment using an automated process. Sterile devices are provided with a certificate of quality.

Faster flow rate

33 mm Millex® filters have 20% more filter surface than 25 mm filters for significantly higher flow rate and throughput. The 33 mm Millex has the same hold-up volume as the 25mm Millex.

Higher operating pressure

With a maximum housing pressure of 150 psig (10 bar), solutions can be filtered faster.


Low extractables, low binding

A variety of membranes and housings ensure chemical compatibility with a range of samples and solvents

Anatomy of a 33 mm Millex® filter

Reliable syringe filtration requires thoughtful device engineering that incorporates robust housing design features which will:


- Prevent leakage
- Minimize holdup volume
- Ensure high particle retention
- Tolerate high operating pressures
- Reduce extractables



Sterile Millex® Syringe Filters

Membrane	Pore Size (µm)	Diameter (mm)	Process Volume (hold-up)	Housing, sterilization method	Connections (inlet outlet)	10 PK	25 PK	50 PK	100 PK	250 PK	
PES Millipore Express® Plus Membrane Fast flow and low binding for cell culture media preparation	0.22	25	100 mL (< 100 µL)	PVC, EO	FLL MLS			SLMPR25SS			
		33	200 mL (< 100 µL)	Modified acrylic, RS	FLL MLS			SLGPR33RS		SLGPR33RB	
	0.45	33	200 mL (< 100 µL)	Modified acrylic, RS	FLL MLS			SLHPR33RS		SLHPR33RB	
		33	100 mL (< 100 µL)	Modified acrylic, RS	FLL MLS			SLVVR33RS			
PVDF Durapore® Membrane Lowest binding for protein rich solutions	0.22	4	1 mL (< 10 µL)	HDPE, EO	FLL Male stepped				SLGV004SL		
		13	10 mL (< 25 µL)	HDPE, EO	FLL MLS				SLGVR13SL		
		25	100 mL (< 100 µL)	PVC, EO	Vented FLL MLS				SLGVVR255F		
	0.45	33	100 mL (< 100 µL)	Modified acrylic, RS	FLL MLS				SLGVR33RS	SLGVR33RB	
		4	1 mL (< 10 µL)	HDPE, EO	FLL Male stepped					SLHV004SL	
		13	10 mL (< 25 µL)	HDPE, EO	FLL MLS					SLHVR13SL	
	5.0	33	100 mL (< 100 µL)	Modified acrylic, RS	FLL MLS				SLHVR33RS	SLHVR33RB	
		25	100 mL (< 100 µL)	PVC, EO	FLL MLS				SLSV0R25LS		
	PVDF Durapel™ Membrane Superhydrophobic for air venting and gas filtration	0.22	25	N/A	PVC, EO	FLL MLL			SLGVS R25US		
	MCE MF-Millipore™ Membrane Most referenced general purpose membrane	0.22	25	100 mL (< 100 µL)	PVC, EO	Vented FLL MLS			SLGSR255F		
33			100 mL (< 100 µL)	Modified acrylic, EO	FLL MLS			SLGSR33SS		SLGSR33SB	
0.45		33	100 mL (< 100 µL)	Modified acrylic, EO	FLL MLS			SLHAR33SS		SLHAR33SB	
		33	100 mL (< 100 µL)	Modified acrylic, EO	FLL MLS			SLAAR33SS		SLAAR33SB	
Hydrophilic PTFE Membrane Broad chemical compatibility	0.2	13	10 mL (< 25 µL)	HDPE, EO	FLL MLS				SLLG013SL		
		25	100 mL (< 100 µL)	HDPE, EO	FLL MLS				SLLG025SS		
PTFE Fluoropore™ Membrane Hydrophobic for gas and alcohol filtration	0.2	25	100 mL (< 100 µL)	PVC, EO	FLL MLS			SLFGR25LS			
					FLL MLL			SLFGL25BS			
					FLL MLS with Needle		SLFGNR25VS				

Pore Size Sterile Syringe Filter Comparison for IgG Protein binding
Average Binding (µg/cm²), n = 4



CA=cellulose acetate;
MCE=mixed cellulose esters;
PVDF=polyvinylidene fluoride;
PES=polyethersulfone

Large-scale Sterile Filtration Devices

Sterivex® Filters

Pressure-driven devices for filtering up to 2 L

Sterivex® filter units work with syringes, peristaltic pumps, or pressure vessels, and are designed to dispense into any storage container.



Description	Process Volume (mL)	Membrane	Pore Size (µm)	Fitting Outlet	Qty/Pk	Cat No.
Sterivex®-GP Filter Units						
Sterivex®-GP Filter Unit	2000	Millipore Express® PLUS (PES)	0.22	Filling Bell	10	SVGPB1010
				Male Luer-Lok®	15	SVGPL10RC
				Male Nipple	15	SVGP01015
					50	SVGP01050
Sterivex®-GV Filter Units						
Sterivex®-GV Filter Unit	1000	Durapore® (PVDF)	0.22	Filling Bell	10	SVGVB1010
				Male Luer-Lok®	15	SVGVL10RC
				Male Nipple	15	SVG01015
					50	SVG010RS
Sterivex®-HV Filter Units						
Sterivex®-HV Filter Unit	1000	Durapore® (PVDF)	0.45	Filling Bell	10	SVHVB1010
				Male Luer-Lok®	15	SVHVL10RC
				Male Nipple	15	SVHV01015
					50	SVHV010RS

Stericap™ PLUS Filters

Universal bottle-top devices for filtering 2 to 10 L

- Fits on any vacuum-rated bottle, 20 to 67 mm in diameter
- Vented to help prevent filter air lock
- Features fast-flowing, low protein binding Millipore Express® PLUS membrane
- Ideal for fast sterilization of tissue culture media, serum, buffers, or other biological solutions

Description	Membrane	Pore Size (µm)	Qty/Pk	Cat No.
Stericap™ PLUS Filter	Millipore Express® PLUS (PES)	0.22	10	SCGPCAPRE



Millex®-GP 50 mm Pump-Driven Filters

Sterilized and individually packed

Description	Pore Size (µm)	Type	Process Volume (mL)	Hold-up Volume (after air purge, mL)	Sterilization Method	Qty/Pk	Cat No.
50 mm Diameter							
Millipore Express® PLUS (PES) Membrane	0.22	GP50	4000	< 1	RS	10	SLGP05010
		GP50 with filling bell				10	SLGPB5010
Glass Filter for Prefiltration	NA	AP	4000	<1	Autoclavable	10	SLAP05010

†EO = ethylene oxide

Steripak™ Filters

Pump-driven filters for volumes up to 20 L

Steripak™ filters are designed for larger scale pressure-driven filtration of tissue culture media, with or without serum. The units are single-use and come in two volume sizes. They are supplied sterile and ready to connect to a pump or pressure vessel.



Description	Membrane	Pore Size (µm)	Filter area, cm ²	Qty/Pk	Cat No.
Steripak™-GP10 Filter	Millipore Express® (PES)	0.22	100	3	SPGPM10RJ
Steripak™-GP20 Filter	Millipore Express® (PES)	0.22	200	3	SPGPM20RJ

Hydrophobic Millex® Filters for Gas Filtration

Description	Application	Pore Size (µm)	Sterility	Inlet-Outlet Fitting	Qty/Pk	Cat No.
Millex® 25 mm Diameter Filters						
Hydrophobic PTFE	Vacuum line protection and gas filtration	0.2	Ethylene oxide	FLL-MLS	50	SLFGR25LS
				FLL-MLL	50	SLFGL25BS
			Autoclavable	FLL-MLS	50	SLFG02550
Hydrophobic PVDF	Transducer protector	0.22	Ethylene oxide	FLL-MLL	50	SLGVSR25US
Pump-driven Millex® 50 mm Diameter Filters						
Hydrophobic PTFE	Vacuum line protection and gas filtration	0.2	Autoclavable	Stepped Hose Barb	10	SLFG05010
					100	SLFG05000
				Stepped Hose Barb – 1/8 in. NPTM	10	SLFG55010
					100	SLFG55000
		1/8 in. NPTM	10	SLFG75010		
			100	SLFG75000		
		0.45	Autoclavable	Stepped Hose Barb	10	SLFH05010
					100	SLFH05000
1.0	Autoclavable	Stepped Hose Barb	10	SLFA05010		
			100	SLFA05000		

FLL = Female Luer-Lok®
 FLS = Female Luer slip
 MLL = Male Luer-Lok®
 MLS = Male Luer slip

Test Kit

Description	Cat No.
Integrity test kit for bubble-point testing of small filter units, such as Millex® and Sterivex® units	SLTEST000

Accessories for Stericup® and Steritop® Systems

For pressure-driven filtration (such as Steripak® and Sterivex®), pressure vessels and pressure peristaltic pumps are available. Please contact Technical Service for further information.

Description	Size	Qty/Pk	Cat No.
Glass fiber prefilters	75 mm	100/pk	AP2007500
Silicone rubber tubing, 3/16 in. (4.8 mm) ID, with adapter	4.5 ft (1.4 m)	1/pk	XX7100004
Vacuum/Pressure Pump 115 V, 60 Hz	N/A	1/pk	WP6111560
Vacuum/Pressure Pump 100 V, 50/60 Hz	N/A	1/pk	WP6110060
Vacuum/Pressure Pump 220 V, 50 Hz	N/A	1/pk	WP6122050
Millivac-Maxi Vacuum Pump, 230 V	N/A	1/pk	SD1P014M04
Millivac-Mini Vacuum Pump, 230 V	N/A	1/pk	XF5423050
Millivac Mini Vacuum Pump, 115 V	N/A	1/pk	XX5411560

Related Products: Multiwell Plates

MultiScreen®_{HTS} Filter Plates

Automation-compatible MultiScreen® filter plates that contain a microporous membrane are ideal for clarifying samples or separating suspensions in diverse workflows, including sample clean-up prior to instrument analysis, removal of cellular debris, extraction of natural products and bead washing for immunoassay procedures.

Membrane	Pore Size	Type	Well Number	Plate Color	Plate Material	Qty/Pk	Cat. No.
Hydrophilic Durapore® PVDF	0.22 µm	GV	96	Clear	Acrylic	10	MSGVS2210
	0.45 µm	HV	96	Clear	Styrene	10	MSHVS4510
	1.2 µm	BV	96	Clear	Styrene	10	MSBVS1210
Hydrophobic Immobilon®-P PVDF	0.45 µm	IP	96	Clear	Acrylic	10	MSIPS4510
	0.45 µm	IP	96	White	Acrylic	10	MSIPS4W10
Hydrophilic MCE	0.45 µm	MCE	96	Clear	Styrene	10	MSHAS4510
	0.45 µm	MCE	96	White	Barex®/TiO2	10	MSHAS4B10

Millicell® Microporous Membrane-Based Cell Culture Plates

Millicell® plates feature membranes that allow easy access to both the apical and basolateral sides of cells. This encourages three-dimensional growth and provides a more accurate *in vitro* model than traditional plastic plates. Both the 24-well and 96-well cell culture plates incorporate patented design features simplifying media exchange for high performance cell-based assays. The plates simplify handling of multiple samples simultaneously, maintain assay integrity, and prevent monolayer disruption during analysis. The assemblies include a choice of a multi-well or single-well feeder tray.

Membrane	Pore Size	Plate Material	Qty/Pk	Cat. No.
Millicell®-24 cell culture plate	24-well cell culture plate, 24-well receiver tray and lid	PCF (3.0 µm)	5	PSST010R5
		PCF (5.0 µm)	5	PSMT010R5
		PCF (8.0 µm)	5	PSET010R5
	24-well cell culture plate, single-well feeder tray and lid	PCF (0.4 µm)	5	PSHT010R5
		PET (1.0 µm)	5	PSRP010R5
		PCF (0.4 µm)	5	PSHT004S5
Millicell®-96 cell culture plate	96-well cell culture plate, 96-well receiver tray and lid	PCF (0.4 µm)	5	PSHT004R5
		PCF (0.4 µm)	5	PSHT004R5
		PET (1.0 µm)	5	PSRP004R5



Millipore®

Preparation, Separation,
Filtration & Monitoring Products

Merck KGaA
Frankfurter Strasse 250
64293 Darmstadt, Germany

MerckMillipore.com

To place an order or receive technical assistance in Europe, please call Customer Service:

France: 0825 045 645

Spain: 901 516 645 Option 1

Germany: 069 86798021

Switzerland: 0848 645 645

Italy: 848 845 645

United Kingdom: 0870 900 4645

For other countries across Europe, please call: +44 (0) 115 943 0840

Or visit: [MerckMillipore.com/offices](https://www.MerckMillipore.com/offices)

For Technical Service visit: [MerckMillipore.com/techservice](https://www.MerckMillipore.com/techservice)

© 2022 Merck KGaA, Darmstadt, Germany and/or its affiliates. All Rights Reserved. Merck, the vibrant M, Millipore, Durapore, MultiScreen, Millicell, Fluoropore, Millex, Millicell, Millipore Express, Stericup, Stericup E, Stericap, Steriflip, Steripak, Steritop, Steritop E and Sterivex are trademarks of Merck KGaA, Darmstadt, Germany or its affiliates. All other trademarks are the property of their respective owners. Detailed information on trademarks is available via publicly accessible resources.