



# Water Sensor

## Control over feed water supply

### General Description

Water sensors exist in 2 versions; they can be connected to the water system or to the main water supply. Their sensors can be placed where most convenient for the lab, typically on the floor or benchtop. In the unlikely event of a leak, the water sensor will detect the presence of water and automatically shut down the feed water access whether it be the system or main water supply.

### Key Benefits

- Greatly reduces risk of flooding: no damage to the lab or other instruments
- Cable length: 4 metres



### Ordering Information

| Description                          | Cat. No.                               |
|--------------------------------------|--|
| Connection from the system           | ZFWATDET4                              |
| Connection from the tap water source | ZFWATDET1 (120 V)<br>ZFWATDET2 (230 V) |
| Water sensor with cable              | TANKLK002                              |

### To place an order or receive technical assistance

In Europe, please call Customer Service:

France: 0825 045 645  
Germany: 069 86798021  
Italy: 848 845 645  
Spain: 901 516 645 Option 1  
Switzerland: 0848 645 645  
United Kingdom: 0870 900 4645

For other countries across Europe, please call: +44 (0) 115 943 0840

Or visit: [merckmillipore.com/offices](http://merckmillipore.com/offices)

For Technical Service visit:  
[merckmillipore.com/techservice](http://merckmillipore.com/techservice)  
[merckgroup.com/life-science](http://merckgroup.com/life-science)

The life science business of Merck operates as MilliporeSigma in the U.S. and Canada.

© 2018 Merck KGaA, Darmstadt, Germany and/or its affiliates. All Rights Reserved. Merck, Milli-Q, and the vibrant M are trademarks of Merck KGaA, Darmstadt, Germany or its affiliates. All other trademarks are the property of their respective owners. Detailed information on trademarks is available via publicly accessible resources.

MK\_DS1254EN  
2017 - 08107  
1/2018